

# Globe Trotter

Auto Folding with lithium battery

- Ultra-lightweight lithium battery
- Fast and easy to fold at a press of a button, with a total unfolding time of under 10 seconds
- Lightweight aluminium frame and components
- Easy on and off charging with excellent access to the battery
- Four-wheel design and high ground clearance offers safe & stable driving



# Globe Trotter

Revolutionarily designed to fulfil many needs, the Globe Trotter is a life-changer. This innovative design ensures that a touch of a button lets you fold up your scooter making it around a third of the size of a normal boot scooter, great for homes with limited space. The light-weight design and ability to fold makes it a great travel companion on any trip, near or far. With the total unfolding time taking under 10 seconds, Globe Trotter is ready anytime for all those travelling needs, creating a more relaxed and carefree atmosphere. Recharging with the ultra-lightweight lithium battery is simple and easy as it can be removed whether the scooter is folded or unfolded and taken to an accessible location. You can also charge through the easy-access tiller charging point. The Globe Trotter can be manoeuvred in the folded position making it effortless to move. Four-wheel design offers more stability with higher ground clearance, making it one of the safest folding scooters available. Adjusting the driving control position is simple giving plenty of leg-room for all users. Air safe deluxe carry bags are available to purchase which ensures carrying the scooter is simple and straightforward.

## Specifications

Model	Globe Trotter
Speed (max)	4mph
Travel Range (max)* - Standard	10mi. (16km)
Battery (max) - Standard	2x 12V x 12Ah AGM
Battery (max) - Endurance	1 x 24V x 10Ah Lithium
User Weight (max)	18 st. (115 kg)
Total Weight (without batteries )	26 kg
Total Weight (with batteries)	28 kg
Overall Length	1000 mm (39.5 in.)
Overall Width	540 mm (21 in.)
Overall Height	890 mm (35 in.)
Folder Height	L460xW540xH660
Climbing Gradient (Max)	12°
Turning Radius (min)	1570 mm (62 in.)
Ground Clearance (Mid Frame)	90 mm (3.5 in.)
Seat	Padded with arms
Seat Width	460 mm (18 in.)
Seat Height	410 mm (16 in.)
Front Tyre	163 mm (6.5 in.) Puncture Proof
Rear Tyre	190 mm (7.5 in.) Puncture Proof
Charger	2 Amp Lithium
Charger Type	Tiller/Battery Pack

\*subject to user weight and terrain



Fast and easy to fold



Ultra lightweight battery pack



Four-wheel design